

Rhenodecor Imprägniergrund, Impregnation Primer

Rhenocoll Lösemittel-**Klassik** Industrieprodukt, solvent-based **Klassik** industrial product

Art.-No.: A 3070

Specification: Wood protection primer, solvent-based, colorless. For exterior wood. Also suitable interior for roof trusses, prefabricated construction, claddings. Shall not be used for other interior wood. Not suitable for wood that comes in contact with feed or food. Free of biocidal agents.

Application: By brush or dipping, spraying in stationary facilities. Manual processing. For professional use.

Supply form / color shade: colorless

Surface: All softwoods and hardwoods.

Further Treatment: Layer forming varnishes (solvent-based and water-based), especially for Rhenocoll "Klassik" coating products as well as the Rhenocoll "Premium" system products.

Consumption: 120 – 160 ml/m²

VOC directives 2010: Cat. H / base lb / max value 750 g/l / actual value 699 g/l

Application Note: The wood to be treated has to be at least semi dry. The substrate has to be clean. Remove paint residues. Coat at least in two working processes, treat dry cracks especially careful. After drying the product is odorless. While and after processing rooms shall be well ventilated. Cover plastic, rubber, bituminous, and other material. Can be recoated after 24 hours at standard conditions (20°C, 65% relative humidity). Depending on the kind of wood, temperature, and weather conditions the drying time can vary or be delayed. Use Rhenodecor products or Rhenocryl varnishes for decorative further treatment. Cover dipping tanks, firmly close original container before storing over a certain period airtight. Use suitable working vessels.

Cleaning of the tools: With Rhenodecor-Verdünner (thinner) or Verdünner 140/1400 (thinner 140/1400)

Storage: Re-close original container firmly, frost-free, dry.

Labeling: Please observe the safety data sheet.

Safety notes: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet.

Packing:

750 ml can

2,5 l paint bucket
5 l paint bucket
30 l hobbock

VOC 2010: does not apply

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: **++49 (0)6384 99 38 - 0**
Fax: **++49 (0)6384 99 38 - 112**
Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case. With the release of this Technical Data Sheet all previous versions become obsolete.