Technical data sheet Agua-Haftgrund GA 11-F, Konzentrat Art.-Nr.: A2512



Version: 2009/06 page 1 of 2

Aqua-Haftgrund, GA 11- F, colorless, primer, concentrate

Art.-Nr.: A 2512

Specification: colorless primer for improving adhesion, interior and exterior, translucent after drying. Improves adhesion between the subsurface and a new paint or plaster. Helps to take the stress during the drying process to avoid flaking. Eco-friendly, water- based.

For professional use.

Application: by roller or brush

Color: colorless

Subsurface: For non-absorbent subsurfaces. Onto old coating, water- based or oil-

based.

Post treatment: Wall and façade coating, plaster

VOC directives 2010: cat H /base Wb /max value 30g/L /actual value 12g/L

Application:

Use: must be mixed 1: 1 with water

Processing condition: Air- and object temperatures must not fall below 8° C

Consumption: approx. 10,0 m²/liter. Surfaces with great absorption

accordingly less

Drying time: May be varnished after 1 - 2 hours after drying at 20° C and

65% humidity. Dries hard and is loadable after approx. 3 days. When lower temperature and higher air humidity the

drying time becomes longer.

General hint: Stir before use or long breaks. Do not mix in solvent

products.

Flashpoint: n/a

Hazard class: No labeling

VbF class: not applicable

Gef. Stoff V: no labeling required, GGVS / ADR: no labeling required

Subsurface pretreatment:

The subsurface must be clean, dry and free of seperative substances. Note VOB, part C, Regard DIN 18363.

Storage:

Do not transport original containers not below +10°C and do not store for a longer period of time above + 30°C. Seal well. An unopened original container storable for 12 months.

Technical data sheet Aqua-Haftgrund GA 11-F, Konzentrat Art.-Nr.: A2512



Version: 2009/06 page 2 of 2

Packing size:

1.0 liter can

5.0 liter container

25.0 liter container

150 liter barrel

Disposal:

Not fully dried and dried paint remains must be disposed as special waste. (AVV- waste code 030202). Recycle empty containers.

Ecology:

WGK = 1 (Self-classification). Do not discharge into the drains / surface waters / groundwater.

Safety hints:

Keep under lock and out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, wash thoroughly with water

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0 Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.