Technical Data Sheet

Aqua-Sandsteinimprägnierung GA 18-0 Art. No: A2550



Version: 2014/09 page 1 of 2

Aqua-Sandsteinimprägnierung GA 18-0, concentrate, stone impregnation Art. No: A 2550

Specification: For the impregnation of mineral substrates, such as stone, sandstone and concrete. Eco-friendly, water- based. Solidifies the surface with a thin film. Reduces the absorption of salts and chlorides from rain and air. Ideal for natural stone with fine and large pores. Very hydrophobic, allows water to easily run off and protects the substrate from humidity. Emphasizes the color of the stones.

Application: Aqua-Sandsteinimprägnierung GA 18-0 can be applied by roller, brush or Airless spray gun. The concentrate needs to be diluted with water 1:1 then it is ready to use. Apply in two coats to guarantee the complete impregnation effect. Before coating, adhesion and appearance should be tested on a large surface area. For professional use.

Supply form / color: colorless

Appearance: wet effect, satin matt

Substrate: Mineral and alkaline substrates, such as mortar, plaster, porous concrete, concrete, sand lime stone, natural stone, industrially manufactured tiles and clinker brick.

Consumption: approx. 5-10 m²/liter per coat, depending on absorption capacity of the substrate

VOC 2010: cat H / base wb / max value 30g/L / actual value 26g/L

Processing:

Use: dilute concentrate with water at a ratio of 1:1

Processing condition: air and object temperatures must be more than +8° C

Drying time: at 20° C and 65% rel. humidity dust dry after 1-2 hours.

Resistant against rain after 4 hours. At lower temperatures

and higher humidity drying time will be longer.

Cleaning of the tools: with water

General note: Stir before use or long breaks. Do not mix with solvent-based

products.

Storage: Protected from direct sunlight; store at temperatures between +5° C and +25 °C in original container approx.1 year from delivery date. Use quickly after opening the container.

Labeling: No labeling

Safety Notes: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the current safety data sheet.

Technical Data Sheet Agua-Sandsteinimprägnierung GA 18-0 Art. No: A2550



Version: 2014/09 page 2 of 2

Supply units:

5 liter canister 25 liter canister

Service: Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0 Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.