

Rhenocoll Haftgrund WD, adhesion primer, concentrate

Specification: Water-based colorless for improved adhesion, interior and exterior, translucent after drying. Improves the adhesion between substrate and coating of plastering. Aids the absorption of stress during drying and the avoidance of chipping. Ecologically friendly, water-based. For subsurfaces which are treated with Dachhaut or Composit. For professional use.

Application: by roller, brush or spray-gun

Supply form/color:
almost colorless

Substrate: For substrates such as plaster, concrete, asbestos cement, wood, brickwork and mineral boards.

Further treatment: Further treatment with Dachhaut (roof coating) Premium or Dachhaut (roof coating) Thermo.

Consumption: approx. 5-6 m²/liter per single coat. Corresponding to approx. 200 g/m², calculated with the ready-to-use mixed product. Before processing, dilute concentrate with water: 1 part Haftgrund WD + 3 parts water. Apply 1-2 coats depending on substrate. Depending on subsurface apply 1-2 coatings.

VOC directive 2010: Cat H / base wb / max value 30 g/L / actual value 5 g/L

Application ranges:

For exterior and interior substrates. For surfaces like plaster, cement, asbestos cement, brickwork, lime sand brick. Particularly suitable for renovation application. Excellent adhesion. For professional use.

Features:

Dilution with water, solvent-free dispersion glaze in high pigmentation, to be used as mass tone application or to be mixed with white paint. Bridges cracks, resistant to wiping and wet abrasion. Easy to process. Formaldehyde-free, halogen-free. Conserved heavy metal free.

Technical hints:

Processing	1:3 dilution with water
Processing temperature	not below + 8° C (temperature of material, circulating air and room)
Consumption	approx. 5-6 , ² per liter. On surface with great absorption accordingly less.
Drying time	At + 20°C and 65 % rel. humidity the surface will be dry and ready to coat after approx. 1-2 hours. Completely dry and tough after approx. 3 days. At a low temperature and higher humidity the times

General hint:	will be extended. Low temperature and higher humidity accordingly longer drying period stir before use and after longer breaks, do not mix with solvent products.
Flash point:	none
Hazard class:	labeling not obligated VbF: not applicable, Gef. Stoff V: labeling not required GGVS / ADR: labeling not required

Surface coating system:

The surface must be clean, dry, oil-free, free of grease and sustainable. Remove non-sustainable or peeling surfaces. Note VOB, part C, DIN 18363, par.3.

Storage:

Do not store or transport in original container below +10°C or for a longer time over 30°C, close well. Storable in non-opened original container for 12 months.
Use once opened container shortly.

Supply units:

1.0 liter pail
5.0 liter pail
25.0 liter barrel
150.0 liter barrel

Disposal:

Use remaining content or let dry up; afterwards dispose in domestic waste.
Dispense liquid material remains to a collection point for old varnishes.

Ecology:

Do not empty into drains, waters or grounds. Avoid eating, drinking and smoking during the application.

Safety hint:

Also during the processing of environment-friendly lacquers, usual safety measures must be observed. Store inaccessible for children. Do not inhale spraying mist. Provide sufficient ventilation during and after processing. Rinse immediately if contact with eyes or skin occurs.

Service:

Our counselling service for technical applications is ready to help you at any time without obligation.

Tel.: + 49 (6384) 9938-110
Fax: + 49 (6384) 9938-112
E-Mail: info@rhenocoll.de

This information is given without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. In any case we recommend that users make their own tests since we have no influence over the large variety of materials and their use. No liability for the manufacturer can be derived from the contents of this notice. Statements going beyond or deviating from the contents of this notice requires the written confirmation of the company headquarters. In all cases our General Terms of trade and delivery are in effect. With the appearance of this Technical Notice all previous versions become invalid.