

Rhenocoll Schimmelstop, concentrate, additive against mould and fungal decay **Art. No.: A 5066**

Specification: Concentrate for fungicidal protection of water-based binding agents, dispersions, façade paints and plaster. Can be used undiluted as a coating for affected areas. Always top-coat with a film forming paint, e.g. wall and façade paint.

Consumption: ca. 750 ml sufficient for 20 liter dispersion paint

Application areas:

Up to 2% of Rhenocoll Schimmelstop can be added to all interior wall paints.
For professional use.

Properties:

Can be added to all interior wall paints in order to add biocidal features. After application, those products have are protected against for mould and fungi.

Storage:

Storable for at least 1 year. Close once opened containers well. Store cool but frost free.

Disposal:

Non-dried product remains must be disposed as special waste (AVV waste key no. 030205). Recycle empty packaging.

Supply form:

750 ml container

VOC directive 2010: not applicable

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.