

Montana GLANZLATEX, IW 49, latex paint for interior use, glossy

Montana GLANZLATEX, IW 49, Color Mix, colored interior paint

Montana GLANZLATEX, IW 49, Base colors A,B,C

- latex paint, glossy, washable, very stress-resistant
- dispersion paint, drip- and spray-inhibited
- wet abrasion resistance according to DIN EN 13300, class 1
- covering power according to DIN EN 13300, class 1
- solvent-free

Art.-No.: A 5044 (latex paint, white)

Art.-No.: A 5180 (Color Mix)

Art.-No.: A 5214 (Base A), A 5216 (Base B), A 5218 (Base C)

Specifications: Especially hard-wearing latex interior wall paint based on latex dispersion, fine texture, particularly abrasion-resistant, glossy. White for wall and ceiling, excellent covering power. Has an hygienic effect to the air in the room. Ecologically friendly, water-based.

Application: by brush, roller or spray-gun

Classification: covering power grade 1, wet wiping resistance grade 2, according to DIN EN 13300.

Color: white and colors with the ColorMix system (using base paint)

Substrate: For interior use, plaster, cement, brickwork, paper and wood-chip wallpaper, plasterboard, as well as for painting of intact old coatings based on dispersion or oil-based. Particularly suitable for glass décor fabric.

Further processing: not applicable

Consumption: approx. 8m²/liter per single coat

VOC directive 2010: Cat B/ base wb/ max value 100g/L/ actual value 20g/L

Application areas:

For internal coating in inhabited and uninhabited rooms. For interior plaster, plaster, plasterboard, cement, hard-fiber and foam board and wallpapers. For professional use.

Properties:

Water-based, solvent-free dispersion paint, ecologically friendly and of low odor. Wash- resistant, excellent covering power, for all interior wall and ceiling surfaces, for high strain. Free from formaldehyde and halogen. Heavy-metal- free preservation. Washable. High-gloss. Extremely durable.

Technical notes:

Application method:	by brush, roller or spray devices
Gloss degree:	glossy
Processing temperature:	not below 8° C (temperature of material, ambient air and room)
Consumption:	1 liter sufficient for 7 m ² : on a smooth substrate. More on rough surfaces. Find out the consumption for finely plastic coatings by a trial coating.
Drying time:	At + 20°C and 65 % rel. humidity the surface will be dry after 2-4 hours and re-coatable. Completely dry and cured after approx. 3 days. At lower temperatures and higher humidity drying times will be extended.
Cleaning of tools:	with water immediately after use.
Tinting:	with compatible full tone and tinting pigments.
General hint:	stir before use and after longer breaks, do not mix with solvent-based products.
Flash point:	none
Danger class:	no labeling required VbF: not applicable, Gef. Stoff V: no labeling required GGVS / ADR: no labeling required

Coating system:

The surface to be coated must be clean, dry, free from oil and grease and sustainable. Not sustainable or flaking surfaces must be removed. Please observe VOB (German Construction Contract Procedures), part C, DIN 18363, para. 3. Wash distempers and chalking surfaces completely.

Prepare highly absorbing and critical substrates with Rhenocoll Aqua Tiefgrund, Montana GLANZLATEX IW 49, process undiluted for priming and top coat.

First coat with Montana GLANZLATEX IW 49 – dilute with up to 10% water.
Final coat with Montana GLANZLATEX IW 49 – undiluted.

Storage:

Store in the original container not below 8°C. Do not store or transport for longer periods of time above 30°C. Close firmly. Can be stored in the unopened original container for 6 months. Use opened containers soon.

Supply units:

2,5 liter pail
5 liter pail
15 liter pail
150 liter barrel
1000 liter container

Disposal:

Use leftover paint or leave to dry and then dispose of as household waste. Liquid leftover paint should be disposed of at the waste disposal collecting point for used lacquers.

Ecology:

Do not discharge into the drains / surface waters / groundwater. Avoid eating, drinking and smoking during processing.

Safety Advice:

Even when processing low-emission paints the usual safety measures are to be observed. Keep under lock and out of reach of children. Do not inhale spraying mist. During and after processing sufficient ventilation must be given. In case of contact with eyes or skin rinse immediately with water.

Service:

Our service team for application technology is available to you at any time without obligation.

Tel.: + 49 (6384) 9938-110

Fax: + 49 (6384) 9938-112

E-Mail: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.