

Montana LATEX, IW 45, latex dispersion paint for interior use, easy to clean

Montana LATEX, IW 45, Color Mix, colored interior paint

Montana LATEX, IW 45, Base colors A,C

- white interior paint for wall and ceiling
- latex paint, matt, washable
- dispersion glaze, drop and spray inhibited
- wet abrasion class 2 according to DIN EN 13300
- covering power class 1 according to DIN EN 13300
- solvent-free

Art.-No.: A 5041 (latex paint, white)

Art.-No.: A 5119 (Color Mix)

Art.-No.: A 5240 (Base A), A 5242 (Base C)

Specification: Latex interior wall paint based on a latex dispersion, easy to clean effect, classification for painters & decorators, resistant to wiping, hard-wearing, matt. White, for walls and ceilings. Good opacity. Acts as a sanitizer to the room climate. Ecologically friendly, water-based. For professional use.

Application: by brush, roller or spray-gun

Classification: covering power class 1, wet abrasion class 2, according to DIN EN 13300.

Color: white and colors with full tone color system (Of base colors)

Substrate: For interior use, plaster, cement, brickwork, paper and wood-chip wallpaper, plasterboard, as well as for coating of intact old coatings on dispersion-based or oil-based.

Further processing: not applicable

Consumption: approx. 6m²/liter per single coat

VOC directive 2010: Cat A/ base wb/ max value 30g/L/ actual value 28g/L

Application areas: For internal coating in inhabited and uninhabited rooms. For interior plaster, plaster, plasterboard, cement, hard-fiber and foam board and wallpapers.

Properties: Water-based, solvent-free dispersion glaze, ecologically friendly and nearly odorless. Wash- resistant, excellent opacity, for all interior wall and ceiling surfaces, extremely durable. Formaldehyde free. Halogen-free. Preserved heavy metal free. Washable.

Technical hints:

Application method:	by brush, roll or spray devices
Gloss degree:	matt
Processing temperature:	not under +8° C (temperature of material, circulating air and room)
Consumption:	1 liter is enough for 6 m ² on smooth substrate. On rough surfaces correspondingly more. Find out the consumption for finely plastic coatings by a trial coating.
Drying time:	At +20°C and 65 % rel. humidity the surface will be dry after 2-4 hours and coatable. Completely dry and tough after approx. 3 days. At a low temperature and higher humidity the times will be extended.
Cleaning of tools:	Immediately with water after use.

General notice: Stir well before use and after longer breaks.
Do not mix with products containing solvents.

Tinting: With compatible tinting pigments.

Coating system: The surface to be coated must be clean, dry, free from oil and grease and sustainable. Not sustainable or flaking surfaces must be removed. Please observe VOB (German Construction Contract Procedures), part C, DIN 18363, para. 3. To avoid incrustation, coat wet-in-wet. Not suitable for horizontal surfaces exposed to water. Wash glue-bound distemper or chalky surfaces thoroughly. Newly plastered surfaces should have been left to dry for at least 4 weeks before painting. Absorbent or critical surfaces should be pre-coated with Rhenocoll Aqua Tiefgrund, apply Montana LATEX IW 45 for pre-coat and top coat.

Undercoat: Use Montana LATEX IW 45 diluted with up to 10% water.

Top coat: Use Montana LATEX IW 45 undiluted.

Spray application: Adjust product to spraying viscosity.

Storage: Store in the original container not below +8°C. Do not store or transport for longer periods over +30°C. Close firmly. Can be stored in the unopened original container for 6 months. Use opened containers soon.

Labeling according to regulation (EC) No 1272/2008: no labeling required.

ADR/GGVS: non dangerous goods.

Safety advice: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet. For professional use. Please observe the technical data sheet.

Supply units:

5 liter pail
15 liter pail
150 liter barrel
1000 liter container

Service:

Our service team for application technology is available to you at any time without obligation.

Tel.: + 49 (6384) 9938-110

Fax: + 49 (6384) 9938-112

E-Mail: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case. With the release of this Technical Data Sheet all previous versions become obsolete